



**ULTRACORE DIVISION**  
Bakersfield, California

# ULTRACORE FILTRATION MEDIA COMBO 20-85% LT

## APPLICATION

Combo 20-85% LT Filter Media is designed to be either fabricated into self-supporting Pleated HVAC filters.

## DESCRIPTION

Media is a glass fiber product on a wet laid chopped strand glass mat backed with a non-woven Class 2 fabric.

## ROLL SPECIFICATIONS

Width (inches): Maximum 72  
Length (feet): Standard 400  
Core: Cardboard with 3 inch ID

## VARIATIONS

Colors other than the standard Pink as well as tailored properties are available to meet customer requirements.

---

## PRODUCT

Weight (grams / feet<sup>2</sup>)  
Thickness (inches)  
Pressure Drop (inches WG)<sup>2</sup>  
Average Efficiency (percent)<sup>3</sup>  
Euro Class<sup>3</sup>  
UL Flammability Classification<sup>4</sup>  
Color

## UFM – COMBO 20-85% LT<sup>1</sup>

13.1  
0.18  
0.22  
80-85  
F7  
2  
Pink

<sup>1</sup> Values listed are nominal properties at the time of production. UPF recommends using media within one year of production and further recommends following FIFO (first in – first out) procedures

<sup>2</sup> Pressure drop is measured at a velocity of 35 feet/ minute (fpm) through a 1 foot x 1 foot flat sheet

<sup>3</sup> Pertaining to finished air filter units tested to ASHRAE 52.1 or EN 779. Results may vary depending on filter design and construction.

<sup>4</sup> Filter media, by itself, is not rated by UL. The UL value shown is a potential rating when media is made into a completed air cleaning device designed to meet that classification in UL 900.