



ULTRACORE DIVISION
Bakersfield, California

ULTRACORE FILTRATION MEDIA COMBO 20-95% LT

APPLICATION

Combo 20-95% LT Filter Media is designed to be either fabricated into self-supporting Pleated HVAC filters.

DESCRIPTION

Media is a glass fiber product on a wet laid chopped strand glass mat backed with a non-woven Class 2 fabric.

ROLL SPECIFICATIONS

Width (inches): Maximum 72
Length (feet): Standard 400
Core: Cardboard with 3 inch ID

VARIATIONS

Colors other than the standard Yellow as well as tailored properties are available to meet customer requirements.

PRODUCT

Weight (grams / feet²)
Thickness (inches)
Pressure Drop (inches WG)²
Average Efficiency (percent)³
Euro Class³
UL Flammability Classification⁴
Color

UFM – COMBO 20-95% LT¹

13.2
0.18
0.34
90-95
F8
2
Yellow

¹ Values listed are nominal properties at the time of production. UPF recommends using media within one year of production and further recommends following FIFO (first in – first out) procedures

² Pressure drop is measured at a velocity of 35 feet/ minute (fpm) through a 1 foot x 1 foot flat sheet

³ Pertaining to finished air filter units tested to ASHRAE 52.1 or EN 779. Results may vary depending on filter design and construction.

⁴ Filter media, by itself, is not rated by UL. The UL value shown is a potential rating when media is made into a completed air cleaning device designed to meet that classification in UL 900.