



ULTRACORE DIVISION
Bakersfield, California

ULTRACORE FILTRATION MEDIA UFM – 85.50 UB

APPLICATION

UFM – 85.50 UB Filter Media can be fabricated into either Pleated or Pocket HVAC filters.

DESCRIPTION

Media is a un-backed glass fiber product.

ROLL SPECIFICATIONS

Width (inches): Maximum 72
Length (feet): Standard 500, 600
Core: Cardboard with 2 inch ID

VARIATIONS

Colors other than the standard No Dye or Pink as well as tailored properties are available to meet customer requirements.

PRODUCT

UFM – 85.50 UB¹

Weight (grams / feet²)

13.0

Thickness (inches)

0.50

Pressure Drop (inches WG)²

0.53

Average Efficiency (percent)³

80-85

Euro Class³

F7

UL Flammability Classification⁴

1

Color

No Dye, Pink

¹ Values listed are nominal properties at the time of production. UPF recommends using media within one year of production and further recommends following FIFO (first in – first out) procedures

³ Pertaining to finished air filter units tested to ASHRAE 52.1 or EN 779. Results may vary depending on filter design and construction.

² Pressure drop is measured at a velocity of 35 feet/ minute (fpm) through a 1 foot x 1 foot flat sheet

⁴ Filter media, by itself, is not rated by UL. The UL value shown is a potential rating when media is made into a completed air cleaning device designed to meet that classification in UL 900.