



**ULTRACORE DIVISION**  
Bakersfield, California

**ULTRACORE FILTRATION MEDIA UFM – 95 UB**

APPLICATION

UFM – 95 UB Filter Media can be fabricated into either Pleated or Pocket HVAC filters.

DESCRIPTION

Media is a un-backed glass fiber product.

ROLL SPECIFICATIONS

Width (inches): Maximum 72  
Length (feet): Standard 500, 600  
Core: Cardboard with 2 inch ID

VARIATIONS

Colors other than the standard Yellow as well as tailored properties are available to meet customer requirements.

<b>PRODUCT</b>	UFM – 95 UB <sup>1</sup>
Weight (grams / feet <sup>2</sup> )	6.5
Thickness (inches)	0.25
Pressure Drop (inches WG) <sup>2</sup>	0.40
Average Efficiency (percent) <sup>3</sup>	90-95
Euro Class <sup>3</sup>	F8
UL Flammability Classification <sup>4</sup>	1
Color	Yellow

<sup>1</sup> Values listed are nominal properties at the time of production. UPF recommends using media within one year of production and further recommends following FIFO (first in – first out) procedures

<sup>2</sup> Pressure drop is measured at a velocity of 35 feet/ minute (fpm) through a 1 foot x 1 foot flat sheet

<sup>3</sup> Pertaining to finished air filter units tested to ASHRAE 52.1 or EN 779. Results may vary depending on filter design and construction.

<sup>4</sup> Filter media, by itself, is not rated by UL. The UL value shown is a potential rating when media is made into a completed air cleaning device designed to meet that classification in UL 900.