



ULTRACORE DIVISION
Bakersfield, California

ULTRACORE FILTRATION MEDIA UFM – 95+ B2

APPLICATION

UFM – 95+ B2 Filter Media can be fabricated into either Pleated or Pocket HVAC filters.

DESCRIPTION

Media is a glass fiber product with a non-woven Class 2 fabric.

ROLL SPECIFICATIONS

Width (inches): Maximum 72
Length (feet): Standard 500, 600
Core: Cardboard with 2 inch ID

VARIATIONS

Colors other than the standard Gold as well as tailored properties are available to meet customer requirements.

PRODUCT	UFM – 95+ B2 ¹
Weight (grams / feet ²)	7.2
Thickness (inches)	0.25
Pressure Drop (inches WG) ²	0.43
Average Efficiency (percent) ³	95+
Euro Class ³	F9
UL Flammability Classification ⁴	2
Color	Gold

¹ Values listed are nominal properties at the time of production. UPF recommends using media within one year of production and further recommends following FIFO (first in – first out) procedures

² Pressure drop is measured at a velocity of 35 feet/ minute (fpm) through a 1 foot x 1 foot flat sheet

³ Pertaining to finished air filter units tested to ASHRAE 52.1 or EN 779. Results may vary depending on filter design and construction.

⁴ Filter media, by itself, is not rated by UL. The UL value shown is a potential rating when media is made into a completed air cleaning device designed to meet that classification in UL 900.

Web Site: www.upf-usa.com

Customer Service: upfcustomersvc@upf-usa.com